

## Maximizing the Efficiency of Your Operation

Save both time and money utilizing Lockwood's superior separation capabilities! Use less horsepower and increase your harvesting capacity while minimizing your fleet costs.

- Right or left hand discharge to accommodate each farmer's needs
- Steerable rear wheels allow for shorter turns
- Variable speed hydraulic drive on the rear cross helps eliminate bruising
- Heavy-duty spindles, hubs and rims for longer life
- Heavy-duty trailing coulters to cut the potato vines
- Rear wheel lift for increased angles on the primary and secondary for improved cleaning
- Digger nose available in narrow or wide
- Larger tires for improved flotation
- Available in center pull or offset hitch

Specs	
Models	552, 554
Number of Rows	2, 4
Row Spacing	32" - 38"
Operating Speed	2 - 5 mph
Headland to Turn	14' - 18'
Est. HP (min)	120 - 150
Hydraulic Pressure	1500 - 2500 psi
Base Machine (lbs)	10,000, 14,000



### Side Discharge

Adjustable discharge height and variable speed rear cross allows the deposit of potatoes onto the ground at a consistent, bruise-free height.



### Hitch Options

Offers the flexibility to pull from the center or offset to accommodate each farmer's needs.



### Rear Height Adjustment

Adjustable rear lift allows operator to raise or lower the rear of the machine to accommodate changing conditions, even on side hills.

